FITTING INSTRUCTION

Clamp mark in acc. with		Cables joining	12
ISO	PN		9 7
1	L	Left directional lights	_ 11
2	+	Rear fog lights	17
3	31	Ground	
4	R	Right directional lights	
5	58R	Right side parking lights	
6	54	Stoplights	*
7	58L	Left side parking lights	B
>	12	11	16 C Spring 8

This towbar is designed to assembly in following cars: VW PASSAT Sedan Syncro 4x4 produced since 10.1996 till 09.2000, VW PASSAT Sedan 4-Motion 4x4 produced since 10.2000 till 12.2004, VW PASSAT Estate Syncro 4x4 produced since 05.1997 till 09.2000, VW PASSAT Estate 4-Motion 4x4 produced since 10.2000 till 12.2004, catalogue no. K43 and is prepared to tow trailers max total weight 2200 kg and max vertical load 85 kg.

From manufacturer

Thank you for buying our product. Their reliability has been confirmed in many tests. Reliability of towbar depends also on correct assembly and right operation. For this reasons we kindly ask to read carefully this instruction and apply to hints.

The towbar should be install in points described by a car producer.

The instruction of the assembly

- 1. Disassemble bumper and metal reinforcement (not used any more).
- 2. To chassis members slip elements (pos. 4) in this way, so holes (pos. A) agree with holes in a car and fix using bolts M10x100mm pos. 12 (loosely) see figure.
- 3. To elements (pos. 4) through holes (pos. B) fix elements pos. 5 and 6 and sleeve (pos. 8) using bolts M12x80mm pos. 11 (loosely).
- 4. To in this way prepared elements fix the main bar of towbar (pos. 1) and screw through holes (pos. C) with bolts M14x100mm (pos. 9).
- 5. Tighten all bolts according to the torque shown in the table.
- 6. Assemble the bumper after cut out his fragment in lower part.
- 7. Fix tow-ball (pos. 2) using bolts M12x75mm (pos. 10) from accessories.
- 8. Fix the socket plate (pos. 3) as shown on the drawing.
- 9. Connect electric wires of 7-poles socket according to the instruction of the car. (Recommend to make at authorized service station).
- 10. Complete the paint coating damaged during installation.

Torque settings for nuts and bolts (8,8):							
	25 Nm 85 Nm		55 Nm 135 Nm	0-1			

NOTE

After install the towbar you should get adequate note in registration book (at authorised service station). The car should be equipped with:

- Indicators
- Tow mirrors

After 1000km of exploitation check all bolts and nuts. The ball of towbar must be always kept clear and conserve with a grease.

Towbar accessories:

Towbar accessories:											
Pos.	Name: Main bar Quantity: 1	Pos. 6	Name: Upper Quantity: 2	fish-plate	Pos. 12 Dim.:	Name: Bolt 8,8 B Quantity: 6 M10x100mm	P	Pos. 19 Dim.:	Nome: Plain Quantity: 6 Ø13 mm	washer	0
		Pos. 7 Dim.:	Name: Śruba Quantity: 1 M8x30mm	8,8 B	Pos. 13 Dim.:	Name: Nut 8 B Quantity: 2 M14	(1)	Pos. 20 Dim.:	Name: Plain Quantity: 6 Ø10,5 mm		0
Pos. 2	Name: Tow-ball Quantity: 1	Pos. 8	Quantity: 2	dystansowa	Pos. 14 Dim.:	Name: Nut 8 B quantity: 6 M12	(1)	Pos. 21 Dim.:	Name: Plain Quantity: 2 Ø8,3 mm	. 1	
Pos. 3	Name: Socket plate Quantity: 1	Pos.	Name: Bolt 8 Quantity: 2 M14x100mr		Pos. 15 Dim.:	Name: Nut 8 B ouantity: 2 M10	©	Pos. 22 Dim.:	Name: Spring Quantity: 2 Ø14,2 mm		
Pos. 4	Name: Side bracket Quantity: 2	Pos. 10 Dim.:	Name: Bolt 8 Quantity: 2 M12x75mm	\sim	Pos. 16 Dim.:	Name: Nut 8 B auantity: 1 M8	©	Pos. 23 Dim.:	Name: Spring Quantity: 6 Ø12,2 mm	-	er.
Pos. 5	Name: Lower fish-plate Quantity: 2	Pos. 11 Dim.:	Quantity: 4		Pos. 17 Dim.:	Name: Washer Quantity: 6 Ø40xØ12x2mm	0	Pos. 24 Dim.:	Quantity: 6	-	(D)
		11 Quantity: 4 17 Quantity: 6									



PPUH AUTO-HAK S. J.

Produkcja Zaczepów Kulowych Henryk & Zbigniew Nejman 76-200 SŁUPSK ul. Słoneczna 16K tel/fax (059) 8-414-414; 8-414-413 E-mail: office@autohak.com.pl www.autohak.com.pl

Towing hitch (without electrical set)

Class: A50-X Cat. no. K43

Designed for:

VW PASSAT Sedan Syncro 4x4
– produced since 10.1996 till 09.2000

VW PASSAT Sedan 4-Motion 4x4

produced since 10.2000 till 12.2004

VW PASSAT Estate Syncro 4x4

- produced since 05.1997 till 09.2000

VW PASSAT Estate 4-Motion 4x4

produced since 10.2000 till 12.2004

Technical data: **D**-value: **11.3 kN**

maximum trailer weight: 2200 kg maximum vertical cup load: 85 kg

Approval number acc. to regulations EKG/ONZ 55.01: E20-55R-01 1197

Foreword

This towbar is designed according to rules of safety traffic regulations. The towing hitch is a safety component and can be install only by qualified personnel. Any alteration or conversion of the towing hitch is prohibited and would lead to cancellation of design certification. Remove insulating compound and underseal from vehicle (if present) in the area of the matting surfaces of the towing hitch. The vehicle manufacturer's specifications regarding trailer load and max. vertical cup load are decisive for driving, and values for the towing hitch cannot be exceeded.

D-value formula:

 $\frac{\text{Max trailer weight [kg]} \quad \text{x} \quad \text{Max vehicle weight [kg]}}{\text{Max trailer weight [kg]} + \quad \text{Max vehicle weight [kg]}} \text{X} \frac{9,81}{1000} = \text{D [kN]}$